



MAGNETEC JAPAN LTD.

ULTRA MAGNETIC FORCED-BAR MAGNETS

- **High Efficiency:** Powerful Neodymium Rare Earth Magnet
- **Reasonable Price**
- **Custom Sizes are Available**
- **Withstanding High Temperature**
- **Application:** Wear Resistance, Corrosion Resistance, Non-Adhesiveness, Sanitary

MBN-22-200-FF



MBN-25-250-TT



Surface Material : SUS316L

Surface Material : SUS316L · Titanium

Model	Diameter	Length	Weight
MBN-22-150	φ 22	1 5 0 ^(mm)	4 2 0 ^(g)
MBN-22-200	φ 22	2 0 0	5 6 0
MBN-22-250	φ 22	2 5 0	7 0 0
MBN-22-300	φ 22	3 0 0	8 4 0
MBN-22-350	φ 22	3 5 0	9 8 0
MBN-22-400	φ 22	4 0 0	1 1 2 0
MBN-22-450	φ 22	4 5 0	1 2 6 0
MBN-22-500	φ 22	5 0 0	1 4 0 0

Model	Diameter	Length	Weight
MBN-25-150	φ 25	1 5 0 ^(mm)	5 4 0 ^(g)
MBN-25-200	φ 25	2 0 0	7 2 0
MBN-25-250	φ 25	2 5 0	9 0 0
MBN-25-300	φ 25	3 0 0	1 0 8 0
MBN-25-350	φ 25	3 5 0	1 2 6 0
MBN-25-400	φ 25	4 0 0	1 4 4 0
MBN-25-450	φ 25	4 5 0	1 6 2 0
MBN-25-500	φ 25	5 0 0	1 8 0 0

End shape

-TT M6 Tap Bothend ,

-TF M6 Tap One Side ,

-FF No Tap

REPRESENTATIVE

MANUFACTURING:

MAGNETEC JAPAN LTD.

MAIN OFFICE :

Phone 81-4-2948-9995

FAX 81-4-2948-6628

E-mail: support @ magnetec.co.jp

URL: http://www.magnetec.co.jp

※ Magnetic Flux Density can be designed and conformed to your requirement.

※ Model and Specification subject to change without Notice.